

AT-CONTROL BOARD

Dual-relay Control Board

- 2-relay, 2,100 users
- Multi access modes: Card, Card or PIN, Card with PIN, multi cards/PINs
- Can connect with any Wiegand 26-37bits reader
- Can connect with any keypad reader with 4bits, 8bits(ASCII), or 10 digits Virtual number output
- Pulse Mode, toggle mode
- Support Master Cards
- Support setting Authorizing Cards
- Support setting Panic users
- Integrated door contact detection and alarm output



Technical specifications	
User Capacity	2.100 Zone 1: 2.000 Zone 2: 100
Operating voltage	12V DC
Idle Current	<30mA
Idle Current (with WIFI)	≤100mA
Relay	2
Adjustable realy output time	1 - 99 seconds (seconds default)
Lock output load	2 Amp Maximum
Wiegand Interface input	Wiegand 26 - 37 bits
Wiegand Interface output	Wiegand 26 - 37 bits (for user tranfer)
Environment	Indoor use
Operating Temperature	-40°C - 60°C
Operating Humidity	0%RH - 0%RH
Physical	ABS Shell
Color	Black
Dimensions (LxWxH)	100 x 86 x 26mm
Unit weight	110g
Shipping weight	180g
Warranty	1 year
Article number	4-080410-0001-000

