

BARRIER OPTIONS

Barrier boom lighting

RGB led strip signal lights

- In closed or motion condition of the boom, the LED strip will light up red. In open position, the strip will turn green.
- The signaling rubber with LED strip is slid into the groove of a round barrier arm
- Available by meter
- Voltage: 24VDC
- Power: 14,4 W/m
- MTBF: + 50.000 hours
- IP 65
- Operating temperature: -25°C to +50°C
- Warranty: 2 years
- Article number:
 - Led signalisation by meter - excluding assembly:
 - 3 meters: 1-010100-0033-000-990-00
 - 4 meters: 1-010100-0048-000-990-00
 - 5 meters: 1-010100-0049-000-990-00
 - Power Supply for LED(strip) 24Vdc 30W Max 1.25A:
 - 3-060102-0011-000



LED SIGNAL LIGHTS

- The lamps are mounted so both sides of the barrier are visible. Depending on the settings of the barrierunit, the signalization lighting can light at different moments between the cyclus
- Lighting signalization is always mounted on the middle of a reflecting strip
- The number of lighting points depends on the lenght of the barrier boom:
 - 2,5 m > 2 lighting points
 - 3,5 m > 2 lighting points
 - 4,5 m > 3 lighting points
 - 5,5 m > 4 lighting points
- Power supply: 24 VDC - Consumption: 30 mA
- Warranty: 2 years
- Article number: 4-030301-0003-000

