


FASTFLOW



ALPHATRONICS
innovators in access technology

PAYTER


CONTACTLESS KIOSK PAYMENT UNIT

Payter's contactless desktop payment unit combines modern technology with user-friendly design, making it ideal for applications where speed, reliability, and flexibility are essential.


This compact yet powerful payment solution supports all common contactless payment methods – including NFC, Mifare, and Desfire – and features a bright 3.5" color touchscreen, integrated barcode scanner, and extensive connectivity options such as WiFi, Bluetooth, and Ethernet.

The unit is available as a desktop version but can also be easily integrated into our Alphatronics kiosks.




Technical specifications	
Contactless interface	<ul style="list-style-type: none"> · EMVCo. L1 v33.0 · ISO14443 Type A & B (T=CL) · Mifare Classic protocol · Desfire protocol EV2/3 · ISO18092: Support NFC Protocol
Reading distance (cm)	10 (depending on the type of card or tag)
Processor	<ul style="list-style-type: none"> · ARM Cortex A7 Core Operating at · 528MHz with ARM TrustZone technology
Memory	<ul style="list-style-type: none"> · 256Mb, DDR3-800 · 8Gb eMMC, high-speed DDR
Expansion ports	USB Type C, dual role port capable of powering expansion modules MDB port
Communication ports	RJ45 connector, Ethernet (100BASE-TX, 10base-10) network port, IEEE802.11b/g/n W-LAN
Operating temperature (°C)	-20 tot 55
Storage temperature (°C)	-20 tot 70
Humidity level (%)	10-90 (non-condensing)
LED indicators	4 RGB LEDs
Display	3.5" IPS LCD Display, 320x480 pixels with backlight 256000 colors
Touchscreen	Capacitive touch
Barcode	Integrated barcode scanner
Audio	Internal speaker (mono audio), buzzer
Sensor	<ul style="list-style-type: none"> · Ambient light sensor · Proximity sensor
Card reader color	Black
Compliance / Standards	CE, FCC, RoHS, WEEE, EMVCo, MasterCard, VISA, PCI
Interfaces	WiFi, Bluetooth, LAN, Serial, USB, GPS Location services
Power supply voltage (V)	<ul style="list-style-type: none"> · 12 to 24V · Internal Li-ion battery for security
Impact resistance	IK09
IP rating	IP65
PIN code	Support Pin entry
Cloud	Portal for configuration and login
Personalization	Customizable screens: <ul style="list-style-type: none"> · Idle screen · Thank you screen · Visible logo on all screens
Contactless payment options	
Housing dimensions (H x W x D)	236 x 140 x 87 mm
Housing material	RVS304
Housing coating	RAL7016 Textured varnish (standard color)
Housing tilt angle	23° relative to the front side
Warranty	1 year
Article number	1-081394-0001-000-xxx-30

DIMENSIONS



CUTOUT DIMENSIONS





PAYTER

CONTACTLESS DESKTOP PAYMENT UNIT



DIMENSIONS



Technical specifications	
Contactless interface	<ul style="list-style-type: none"> · EMVCo. L1 v33.0 · ISO14443 Type A & B (T=CL) · Mifare Classic protocol · Desfire protocol EV2/3 · ISO18092: Support NFC Protocol
Reading distance (cm)	10 (depending on the type of card or tag)
Processor	<ul style="list-style-type: none"> · ARM Cortex A7 Core Operating at · 528MHz with ARM TrustZone technology
Memory	<ul style="list-style-type: none"> · 256Mb, DDR3-800 · 8Gb eMMC, high-speed DDR
Expansion ports	USB Type C, dual role port capable of powering expansion modules MDB port
Communication ports	RJ45 connector, Ethernet (100BASE-TX, 10base-10) network port, IEEE802.11b/g/n W-LAN
Operating temperature (°C)	-20 tot 55
Storage temperature (°C)	-20 tot 70
Humidity level (%)	10-90 (non-condensing)
LED indicators	4 RGB LEDs
Display	3.5" IPS LCD Display, 320x480 pixels with backlight 256000 colors
Touchscreen	Capacitive touch
Barcode	Integrated barcode scanner
Audio	Internal speaker (mono audio), buzzer
Sensor	<ul style="list-style-type: none"> · Ambient light sensor · Proximity sensor
Card reader color	Black
Compliance / Standards	CE, FCC, RoHS, WEEE, EMVCo, MasterCard, VISA, PCI
Interfaces	WiFi, Bluetooth, LAN, Serial, USB, GPS Location services
Power supply voltage (V)	<ul style="list-style-type: none"> · 230Vac · Internal Li-ion battery for security
Housing dimensions (H x W x D)	132 x 114 x 150 mm
PIN	Support Pin entry
Cloud	Portal for configuration and login
Personalization	Customizable screens: <ul style="list-style-type: none"> · Idle screen · Thank you screen · Visible logo on all screens
Contactless payment options	
Warranty	1 year
Article number	1-081303-0002-000-000-00

TAILOR-MADE IN BELGIUM

Alphatronics is a **manufacturer** of customised perimeter security solutions with the flexibility to adapt security needs to a specific situation.

In-house development and production, modularly designed to integrate with other business processes. It is in our DNA to **innovate** and in doing so, we always deliver the highest quality.

SOFTWARE INTEGRATION

We feature a **very accessible RESTfull API**. This enables the integration of Alphatronics-supplied hardware devices and a third-party software solution.

INSTALLATION AND SERVICE


With more than **35 years of experience** in installation and service, we offer the expertise for perfect integration of your entire system.

A maintenance contract guarantees that the system will always be up and running.


The helpdesk with professional and fast service is always ready for support.

COUNT ON ALPHATRONICS FOR

- an extensive and innovative product range
- creative and sophisticated solutions
- technical and commercial support
- project strategy
- excellence in system integration



ACCESS FOR
VEHICLES



ACCESS FOR
PEDESTRIANS



OPERATING COLUMNS
& PILLARS



API

